



**ASI 174 Clear Siliconized Acrylic Latex**

<b>Section 1: Product and Company Identification</b>	
American Sealants, Inc. 9190 Yeager Ln Fort Wayne, Indiana 46809 Phone: 260-489-0728 Fax: 260-489-0519	Emergency Phone Number Infotrac: +1-800-535-5053 (Within US) Infotrac: +1-352-323-3500 (Outside US)
Product Identifier:	ASI 174 Clear Siliconized Acrylic Latex
Recommended Use:	Aqueous Clear Sealant w/ Silicone (applies white, dries clear within 2 weeks)
Restrictions on Use:	None known.

<b>Section 2: Hazard(s) Identification</b>	
This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). However, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.	
Acute and Delayed Effects:	Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.
Indication of Immediate Medical Attention and Special Treatment Needed, If Needed:	Treat symptomatically and supportively. May aggravate pre-existing skin disorders.
<b>GHS Label Elements</b>	
Symbol(s):	None.
Signal Word:	None.
Hazard Statement(s):	None known.
Precautionary Statement(s) Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.
Response:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention.

# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
Storage:	Close container after each use. Store containers away from excessive heat & freezing. Do not store at temperatures above 120 °F.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 3: Composition/Information on Ingredients

<u>CAS</u>	<u>Component</u>	<u>Percent</u>
Mixture	Acrylic Emulsion	< 95
Mixture	Acrylic Thickener	< 5
Proprietary	Non-hazardous Ingredients*	< 5
57-55-6	Propylene Glycol	< 1.25
7664-41-7	Ammonium Hydroxide	< 0.25
64742-48-9	Petroleum Hydrocarbon	< 0.50

\*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

## Section 4: First-Aid Measures

Inhalation:	IF INHALED: Remove to fresh air. If breathing difficult, leave area to obtain fresh air. If breathing remains difficult, get medical attention.
Skin Contact:	IF ON SKIN: Wash off with plenty of soap and water while removing all contaminated clothes and shoes. If irritation persists: Get medical advice/attention. Wash contaminated clothing before use.
Eye Contact:	IF IN EYES: Flush eyes with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation develops and persists: Get medical advice/attention.
Ingestion:	Do not induce vomiting, unless directed by medical personnel. Get immediate medical attention if symptoms occur. If vomiting occurs, keep head low so that stomach content does not get into the lungs.

## Section 5: Fire-Fighting Measures

Suitable Extinguishing Media:	Use carbon dioxide, regular dry chemical powder, alcohol-resistant foam, or water fog.
Unsuitable Extinguishing Media:	None known.

### Specific Hazards Arising from the Chemical

Hazardous Decomposition Products: Carbon, titanium and iron oxides, depending upon formulation.

# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

Special Protective Equipment and Precautions for Firefighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained breathing apparatus.
	Product is combustible and may ignite if exposed to high temperature or direct flame.
Specific extinguishing methods:	Use water spray to keep fire-exposed containers cool.

## Section 6: Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:	Wear appropriate personal protective equipment.
Environment Precautions:	Minimize use of water to prevent environmental contamination. Prevent spill or rinse from contaminating storm drains, sewers, soil or groundwater.
Methods and Materials for Containment and Cleaning Up:	Prevent further leakage or spillage if safe to do so. Use absorbent material to contain spill. Sweep up absorbed material and shovel into suitable containers for disposal. Wash area with soap and water. For waste disposal, see section 13 of the SDS.

## Section 7: Handling and Storage

<b>Precautions for Safe Handling</b> Protective Measures:	Avoid breathing vapors. Use only with adequate ventilation. Open windows & doors to ensure fresh air cross-ventilation during application and curing. Avoid contact with skin, eyes or clothing. While handling product keep out of reach of children and pets.
Advice on General Occupational Hygiene:	Do not eat, drink, or smoke when using this product. Wash thoroughly after handling. Wash contaminated clothing before reuse.
Conditions for Safe Storage, including any Incompatibilities:	Close container after each use. Store containers away from excessive heat & freezing. Do not store at temperatures above 120 °F. To maximize shelf life, store at temperatures below 26 °C (80 °F).
Incompatibilities:	Oxidizers and strong acids

# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

<b>Section 8: Exposure Controls/Personal Protection</b>		
<b>Component Exposure Limits</b>		
CAS	Component	Exposure Limits
7664-41-7	Ammonium Hydroxide	<b>ACGIH TLV:</b> 35 ppm STEL; 25 ppm TWA <b>OSHA PEL:</b> 50 ppm TWA; 35 mg/m <sup>3</sup> TWA; (vacated) 35 ppm STEL; (vacated) 27 mg/m <sup>3</sup> STEL <b>NIOSH IDLH:</b> 300 ppm IDLH; 25 ppm TWA; 18 mg/m <sup>3</sup> TWA; 35 ppm STEL; 27 mg/m <sup>3</sup> STEL
<p>Appropriate Engineering Controls: Provide adequate general and local exhaust ventilation.</p> <p><b>Individual Protection Measures</b></p> <p>Eye/Face Protection: Wear tightly sealed safety glasses according to EN 166.</p> <p>Skin Protection: Skin should be washed after contact.                      Body: Use protection appropriate for task (eg: lab coat, coveralls, Tyvek suit). If necessary, refer to OSHA Technical Manual (Sec. VII: Personal Protective Equipment) or appropriate Standards of Canada. Use foot protection, as described in appropriate regulations &amp; standards.</p> <p>Hand Protection: Wear chemical impervious gloves (eg: Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations &amp; standards. Wash hands before breaks and at the end of workday.</p> <p>Respiratory Protection: If mists or sprays are created, use appropriate respiratory protection. Oxygen levels below 19.5% considered IDLH by OSHA. In such instances, use full-face piece pressure demand SCBA or a full face piece, supplied air respirator w/ auxiliary self-contained air supply.</p>		

<b>Section 9: Physical and Chemical Properties</b>	
<b>Physical State:</b> Smooth paste	<b>Appearance:</b> White when applied, paste
<b>Color:</b> White when applied, dries clear < 2 weeks	<b>Physical Form:</b> : Paste
<b>Odor:</b> Mild acrylic, Slight ammoniacal odor	<b>Odor Threshold:</b> Not available
<b>pH:</b> 7.0 – 10.0	<b>Melting Point:</b> < 0 °C / < 32 °F
<b>Boiling Point/Boiling Range:</b> ~98.88 - 104.44 °C / ~210 - 220 °F	<b>Decomposition:</b> Not available
<b>Flash Point:</b> > 93.33 °C / > 200 °F	<b>Evaporation Rate:</b> Not available
<b>OSHA Flammability Class:</b> Not classified as a flammability hazard	<b>Vapor Pressure:</b> Not available
<b>Vapor Density (air = 1):</b> > 1 (air=1)	<b>Density:</b> 1.03 (25 °C)
<b>Specific Gravity (water = 1):</b> ~1.04-1.08 (at 25 °C)	<b>Water Solubility:</b> Soluble in water
<b>Log KOW:</b> Not available	<b>Coeff. Water/Oil Dist:</b> Not available
<b>KOC:</b> Not available	<b>Auto Ignition:</b> Not available
<b>Viscosity:</b> Not available	<b>VOC:</b> < 0.5 %; < 10 g/L

# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

**Volatility:** Not available

**Molecular Formula:** Not applicable

## Section 10: Stability and Reactivity

Reactivity: Cures upon contact with air.

Chemical Stability: Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: Excessive heat or cold. Do not store at temperatures above 120 °F.

Incompatible Materials: Oxidizers and strong acids

Hazardous Decomposition Products: Carbon, titanium and iron oxides, depending upon formulation.

## Section 11: Toxicological Information

### Acute Toxicity

#### Component Analysis – LD50/LC50

CAS	Component	Result	Species	Dose	Exposure
57-55-6	Propylene Glycol	LD50 Oral	Rat	= 2000 mg/kg	N/A
		LD50 Dermal	Rabbit	= 20800 mg/kg	N/A
7664-41-7	Ammonium Hydroxide	LD50 Oral	Rat	= 350 mg/kg	N/A
		LC50 Inhalation	Rat	= 5.1 mg/L = 2000 ppm	1 hr 4 hr
64742-48-9	Petroleum Hydrocarbon	LD50 Oral	Rat	> 5000 mg/kg	N/A
		LD50 Dermal	Rabbit	> 3160 mg/kg	N/A

### Information on Likely Routes of Exposure

Inhalation: Mildly irritating to respiratory tract.

Ingestion: May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.

Skin Contact: Prolonged and frequent contact may cause redness and irritation. Repeated skin contact may cause dermatitis.

Eye Contact: May cause temporary irritation on eye contact.

Immediate and Delayed Effects: Prolonged or repeated skin contact may result in dermatitis (red, dry skin). Direct contact with eyes may cause temporary irritation. Exposed individuals may experience eye tearing, redness and discomfort. Irritating to mouth, throat, and stomach if ingested. May cause gastrointestinal irritation, nausea, diarrhea, and vomiting. Overexposure to vapors during application and curing may mildly irritate respiratory tract and result in coughing and sneezing.

## SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

Medical Conditions Aggravated by Exposure:	May aggravate pre-existing skin disorders.
Irritation/Corrosivity Data:	Not available.
Respiratory Sensitization:	Not known to be human skin or respiratory sensitizers.
Dermal Sensitization:	Not known to be human skin or respiratory sensitizers.
Germ Cell Mutagenicity:	Not available.
Carcinogenicity:	Trace residual Formaldehyde present in base emulsion viewed as possible cancer hazard.
<b>Component Carcinogenicity:</b>	Not available.
Reproductive Toxicity:	Not available.
Specific Target Organ Toxicity – Single Exposure:	Not available.
Specific Target Organ Toxicity – Repeated Exposure:	Not available.
Aspiration Hazard:	Not available.

Section 12: Ecological Information						
<b>Ecotoxicity</b>						
Product not tested for aquatic or animal toxicity. Release of product to terrestrial, atmospheric & aquatic environments should be avoided.						
<b>Component Analysis – Aquatic Toxicity</b>						
CAS	Component	Aquatic	Result	Species	Dose	Exposure
57-55-6	Propylene Glycol	Fish	LC50	Rainbow trout ( <i>Oncorhynchus mykiss</i> )	51600 mg/L	96 hr
			LC50	Rainbow trout ( <i>Oncorhynchus mykiss</i> )	41 - 47 mL/L [static]	96 hr
			LC50	Fathead minnow ( <i>Pimephales promelas</i> )	51400 mg/L [static]	96 hr
			LC50	Fathead minnow ( <i>Pimephales promelas</i> )	710 mL/L	96 hr
		Invertebrates	EC50	Water flea ( <i>Daphnia magna</i> )	10000 mg/L	24 hr

## SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

			EC50	Water flea ( <i>Daphnia magna</i> )	1000 mg/L	48 hr
		Algae	EC50	Green algae ( <i>Pseudokirchneriella subcapitata</i> )	19000 mg/L	96 hr
7664-41-7	Ammonium Hydroxide	Fish	LC50	Common Carp ( <i>Cyprinus carpio</i> )	0.44 mg/L	96 hr
			LC50	Bluegill ( <i>Lepomis macrochirus</i> )	0.26 – 4.6 mg/L	96 hr
			LC50	Bluegill ( <i>Lepomis macrochirus</i> )	1.17 mg/L [flow-through]	96 hr
			LC50	Fathead minnow ( <i>Pimephales promelas</i> )	0.73 – 2.35 mg/L	96 hr
			LC50	Fathead minnow ( <i>Pimephales promelas</i> )	5.9 mg/L [static]	96 hr
			LC50	Guppy ( <i>Poecilia reticulata</i> )	1.5 mg/L	96 hr
			LC50	Guppy ( <i>Poecilia reticulata</i> )	1.19 mg/L	96 hr
		Invertebrates	LC50	Water flea ( <i>Daphnia magna</i> )	25.4 mg/L	48 hr
64742-48-9	Petroleum Hydrocarbon	Fish	LC50	Fathead minnow ( <i>Pimephales promelas</i> )	2200 mg/L	96 hr
		Invertebrates	LC50	<i>Chaetogammarus marinus</i>	2.6 mg/L	96 hr
Persistence and Degradability:		No information available for the product.				
Bioaccumulative Potential:		No information available for the product.				
Mobility in Soil:		No information available for the product.				
<b>CAS</b>	<b>Component</b>				<b>Partition Coefficient</b>	
7664-41-7	Ammonium Hydroxide				-1.14	
Biodegradation:		No information available for the product.				

### Section 13: Disposal Considerations

Disposal Methods:	Dispose in accordance with all applicable federal, state/regional and local laws and regulations.
Disposal of Contaminated Packaging:	Dispose of unused product properly. Empty containers should be taken to an approved waste handling site for recycling or disposal.

# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

Component Waste Numbers:	The U.S. EPA has not published waste numbers for this product's components.
--------------------------	---

<b>Section 14: Transport Information</b>	
<b>International Regulation</b>	
IATA:	Not regulated as a dangerous good.
IMDG:	Not regulated as a dangerous good.
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: This product is not intended to be transported in bulk.	
<b>Domestic Regulation</b>	
DOT:	Not regulated as a dangerous good.

<b>Section 15: Regulatory Information</b>					
<b>US Federal Regulations</b>					
SARA 302 Extremely Hazardous Substances: None contained in product.					
SARA 304: Not applicable.					
SARA 311/312: <b>Acute Health: Yes Chronic Health: No Fire: No Pressure: No Reactive: No</b>					
SARA 313:					
<b>CAS</b>	<b>Component</b>	<b>Weight- %</b>	<b>SARA 313 – Threshold Values %</b>		
76664-41-7	Ammonium Hydroxide	< 0.25	1.0		
TSCA: All components of this product are listed on TSCA Inventory.					
Clean Water Act:					
<b>CAS</b>	<b>Component</b>	<b>CWA – Reportable Quantities</b>	<b>CWA – Toxic Pollutants</b>	<b>CWA – Priority Pollutants</b>	<b>CWA – Hazardous Substances</b>
76664-41-7	Ammonium Hydroxide	100 lb			X
CERCLA Reportable Quantity:					
<b>CAS</b>	<b>Component</b>	<b>Hazardous Substances RQs</b>	<b>CERCLA/SARA RQ</b>	<b>Reportable Quantity (RQ)</b>	
76664-41-7	Ammonium Hydroxide	100 lb	100 lb	RQ 100 lb final RQ RQ 45.4 kg final RQ	
<b>US State Regulations</b>					
Massachusetts Right-to-Know - Substance List:		Ammonium Hydroxide (7664-41-7)			
New Jersey Worker and Community Right-to-Know Act:		Propylene Glycol (57-55-6) Ammonium Hydroxide (7664-41-7)			
Pennsylvania Worker and Community Right-to-Know Law:		Propylene Glycol (57-55-6) Ammonium Hydroxide (7664-41-7)			



# SAFTEY DATA SHEET

Product Identifier: ASI 174 Clear Siliconized Acrylic Latex

Document #: SDS 037

Revision: 1

California Proposition 65: This product does not contain any chemicals known by the State of California to cause cancer or reproductive harm.

### Component Analysis – International Inventories

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Propylene Glycol	57-55-6	Yes	DSL	EINECS	Yes	Yes	Yes	Yes	Yes	Yes
Ammonium Hydroxide	7664-41-7	Yes	DSL	EINECS	Yes	Yes	Yes	Yes	Yes	Yes
Petroleum Hydrocarbon	64742-48-9	Yes	DSL	EINECS	Yes	Yes	Yes	Yes	Yes	Yes

### Section 16: Other Information

Issue Date: 7/7/15

Revision: 1

NFPA Ratings:

Health: 1

Fire: 1

Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECS (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

**End of Document**