




**ASI Aquarium Aluminum**

<b>Section 1: Product and Company Identification</b>	
American Sealants, Inc. 9190 Yeager Ln Fort Wayne, Indiana 46809 Phone: 260-489-0728 Fax: 260-399-5068	Emergency Phone Number Infotrac: +1-800-535-5053 (Within US) Infotrac: +1-352-323-3500 (Outside US)
Product Identifier:	ASI Aquarium Aluminum
Recommended Use:	RTV rubbers (for Aquarium Manufacturing and Repair)
Restrictions on Use:	Industrial use only.

<b>Section 2: Hazard(s) Identification</b>	
<b>Classification in accordance with 29 CFR 1910.1200.</b> Reproductive toxicity (fertility), Category 2	
Acute and Delayed Effects:	Direct contact with eyes may cause temporary irritation.
Indication of Immediate Medical Attention and Special Treatment Needed, If Needed:	Treat symptomatically and supportively.
<b>GHS Label Elements</b>	
Symbol(s):	
Signal Word:	Warning
Hazard Statement(s):	Suspected of damaging fertility.
Precautionary Statement(s) Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.
Response:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Get medical advice/attention if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

# SAFETY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

	Take off contaminated clothing and wash it before reuse.
Storage:	Store locked up.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 3: Composition/Information on Ingredients

<u>CAS</u>	<u>Component</u>	<u>Percent</u>
Proprietary	Acetoxysilane	3 - < 5
556-67-2	Octamethylcyclotetrasiloxane (Impurity)	< 0.2

## Section 4: First-Aid Measures

Inhalation:	IF INHALED: Remove to fresh air. Get medical attention if symptoms occur.
Skin Contact:	IF ON SKIN: Wash off with plenty of soap and water. For minor skin contact, avoid spreading material on unaffected skin. Get medical advice/attention if symptoms occur. Take off contaminated clothing and wash before use.
Eye Contact:	IF IN EYES: Flush eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation develops and persists: Get medical advice/attention.
Ingestion:	Rinse mouth thoroughly with water. Get immediate medical attention if symptoms occur.

## Section 5: Fire-Fighting Measures

Suitable Extinguishing Media:	Use carbon dioxide, regular dry chemical powder, alcohol-resistant foam, or water fog.
Unsuitable Extinguishing Media:	None known.
<b>Specific Hazards Arising from the Chemical</b>	
Hazardous Decomposition Products:	By heating and fire, harmful vapors/gases may be formed.
Special Protective Equipment and Precautions for Firefighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet, gloves, rubber boots, and self-contained breathing apparatus.
Specific extinguishing methods:	Move containers from fire area if you can do so without risk.

# SAFTEY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

## Section 6: Accidental Release Measures

### Personal Precautions, Protective

Equipment and Emergency Procedures: Keep unnecessary personnel away.  
Do not touch or walk through spilled material.  
Ensure adequate ventilation.  
Wear appropriate personal protective equipment.

Environment Precautions: Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

### Methods and Materials for Containment and Cleaning Up:

Eliminate sources of ignition.  
Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.  
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece).  
Clean surface thoroughly to remove residual contamination.  
Never return spills in original containers for re-use.

## Section 7: Handling and Storage

### Precautions for Safe Handling

Protective Measures: Provide adequate ventilation. Use care in handling/storage. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.  
Do not breathe mist or vapor.  
Avoid contact with eyes and skin. Avoid prolonged exposure.

### Advice on General Occupational Hygiene:

Do not eat, drink, or smoke when using this product.  
Wash thoroughly after handling.  
Wash contaminate clothing before reuse.

### Conditions for Safe Storage, including any Incompatibilities:

Store locked up. Keep in original container and tightly closed.  
Keep out of the reach of children.  
Store in a cool, dry place out of direct sunlight.

### Incompatibilities:

Strong oxidizing agents, water, moisture

# SAFTEY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

<b>Section 8: Exposure Controls/Personal Protection</b>		
<b>Component Exposure Limits</b>		
CAS	Component	Exposure Limits
64-19-7	Acetic acid (decomposition product)	<b>ACGIH:</b> 15 ppm STEL; 10 ppm TWA <b>OSHA Z-1:</b> 25 mg/m <sup>3</sup> PEL; 10 ppm <b>NIOSH:</b> 37 mg/m <sup>3</sup> STEL; 15 ppm 25 mg/m <sup>3</sup> TWA; 10 ppm
<p><b>Appropriate Engineering Controls:</b> Provide adequate general and local exhaust ventilation. Provide eyewash station. Pay attention to ventilation such as local exhaust, mechanical and/or door open for at least 24 hours after application.</p> <p><b>Individual Protection Measures</b></p> <p><b>Eye/Face Protection:</b> Wear tightly sealed safety glasses according to EN 166. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.</p> <p><b>Skin Protection:</b> Skin should be washed after contact.</p> <p><b>Hand Protection:</b> Wear protective gloves. Wash hands before breaks and at the end of workday.</p> <p><b>Respiratory Protection:</b> If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection.</p>		

<b>Section 9: Physical and Chemical Properties</b>	
<p><b>Physical State:</b> Liquid</p> <p><b>Color:</b> Aluminum</p> <p><b>Odor:</b> Acetic acid odor</p> <p><b>pH:</b> Not applicable</p> <p><b>Boiling Point:</b> Not applicable</p> <p><b>Flash Point:</b> &gt; 141.8 °F (&gt; 61 °C)</p> <p style="padding-left: 20px;">Closed cup (Does not sustain combustion)</p> <p><b>OSHA Flammability Class:</b> Not classified as a flammability hazard</p> <p><b>Vapor Density (air = 1):</b> &gt; 1 (air=1)</p> <p><b>Specific Gravity (water = 1):</b> Not available</p> <p><b>Log KOW:</b> Not available</p> <p><b>KOC:</b> Not available</p> <p><b>Viscosity:</b> No data</p> <p><b>Volatility:</b> Not available</p>	<p><b>Appearance:</b> Paste</p> <p><b>Physical Form:</b> Paste</p> <p><b>Odor Threshold:</b> Not available</p> <p><b>Freezing/Melting Point:</b> Not applicable</p> <p><b>Decomposition:</b> Not available</p> <p><b>Evaporation Rate:</b> &lt; 1 (Butyl Acetate=1)</p> <p><b>Vapor Pressure:</b> Negligible (25 °C)</p> <p><b>Density:</b> 1.03 (25 °C)</p> <p><b>Water Solubility:</b> Not soluble</p> <p><b>Coeff. Water/Oil Dist:</b> Not available</p> <p><b>Auto Ignition:</b> No data</p> <p><b>VOC:</b> Not available</p> <p><b>Molecular Formula:</b> Not applicable</p>

# SAFTEY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

## Section 10: Stability and Reactivity

Reactivity: Not classified as a reactivity hazard.

Chemical Stability: Stable at normal temperatures and pressure.

Possibility of Hazardous Reactions: Hazardous polymerization does not occur.

Conditions to Avoid: None known.

Incompatible Materials: Strong oxidizing materials, water, moisture

Hazardous Decomposition Products: This product reacts with water, moisture or humid air to evolve following compound: Acetic acid

Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide and Formaldehyde.

## Section 11: Toxicological Information

### Acute Toxicity

#### Component Analysis – LD50/LC50

CAS	Component	Result	Species	Dose	Exposure
64-19-7	Acetic acid (decomposition product)	LD50 Oral	Rat	3.31 g/kg	N/A
			Rabbit	1200 mg/kg	N/A
			Mouse	4960 mg/kg	N/A
		LC50 Inhalation	Rat	11.4 mg/L	4 hr
			Mouse	5620 ppm	1 hr
			Guinea pig	5000 ppm	1 hr
LD50 Dermal	Rabbit	1060 mg/kg	N/A		

### Information on Likely Routes of Exposure

Inhalation: Prolonged inhalation may be harmful.

Ingestion: Expected to be a low ingestion hazard.

Skin Contact: No adverse effects due to skin contact are expected.

Eye Contact: Direct contact with eyes may cause temporary irritation.

Immediate and Delayed Effects: Direct contact with eyes may cause temporary irritation.

Medical Conditions Aggravated by Exposure: No information is available.

## SAFETY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

Irritation/Corrosivity Data:	Causes severe skin burns and eye damage. [Acetic acid] SKIN-RABBIT : 500mg/24 r MILD [Octamethylcyclotetrasiloxane]  Causes serious eye damage. [Acetic acid] EYE-RABBIT : MILD [Octamethylcyclotetrasiloxane]
Respiratory Sensitization:	Not available.
Dermal Sensitization:	No evidence of sensitization [Octamethylcyclotetrasiloxane]
Germ Cell Mutagenicity:	Negative(Bacteria) [Octamethylcyclotetrasiloxane]
Carcinogenicity:	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>Component Carcinogenicity:</b>	Not available.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.	
Reproductive Toxicity:	Octamethylcyclotetrasiloxane administered to rats by whole body inhalation at concentrations of 500 and 700 ppm for 70 days prior to mating, through mating, gestation and lactation resulted in decreases in live litter size. Additionally, increases in the incidence of deliveries of offspring extending over an unusually long time period (dystocia) were observed at these concentrations. Statistically significant alterations in these parameters were not observed in the lower concentrations evaluated (300 and 70 ppm). In a previous range-finding study, rats exposed to vapor concentrations of 700 ppm had decreases in the number of implantation sites and live litter size. The significance of these findings to humans is not known. [Octamethylcyclotetrasiloxane]
Specific Target Organ Toxicity – Single Exposure:	Not available.
Specific Target Organ Toxicity – Repeated Exposure:	Repeated inhalation or oral exposure of mice and rats to octamethylcyclotetrasiloxane produced an increase in liver size. No gross histopathological or significant clinical chemistry effects were observed. An increase in liver metabolizing enzymes, as well as a transient increase in the number of normal cells (hyperplasia) followed by an increase in cell size (hypertrophy) were determined to be the underlying causes of the liver enlargement. The biochemical mechanisms producing these effects are highly sensitive in rodents, while similar mechanisms in humans are insensitive. A two year combined chronic and carcinogenicity assay was conducted on octamethylcyclotetrasiloxane. Rats were exposed by whole-body vapor inhalation 6hrs/day, 5days/week for up to 104weeks to 0, 10, 30, 150 or 700ppm of octamethylcyclotetrasiloxane. The increase in incidence of (uterine) endometrial cell hyperplasia and uterine adenomas (benign tumors) were observed in female rats at 700ppm. Since these effects only occurred at 700ppm, a level that greatly exceeds typical workplace or consumer exposure, it is unlikely that industrial, commercial or consumer uses of products containing octamethylcyclotetrasiloxane

## SAFETY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

	would result in a significant risk to humans. [Octamethylcyclotetrasiloxane]
Aspiration Hazard:	Not available.
Further Information:	This product reacts with water, moisture or humid air to evolve the following compound: Acetic acid

### Section 12: Ecological Information

#### Ecotoxicity

May cause long lasting harmful effects to aquatic life. [Octamethylcyclotetrasiloxane]

#### Component Analysis – Aquatic Toxicity

CAS	Component	Aquatic	Result	Species	Dose	Exposure
64-19-7	Acetic acid	Fish	LC50	Bluegill ( <i>Lepomis macrochirus</i> )	75 mg/L	96 hr
		Invertebrates	EC50	Water flea ( <i>Daphnia magna</i> )	65 mg/L	48 hr

Persistence and Degradability: No information available for the product.

Bioaccumulative Potential: Bio concentration Factor(BCF) / (Fathead minnows) : 12400  
[Octamethylcyclotetrasiloxane]

Mobility in Soil: No information available for the product.

Biodegradation: No information available for the product.

### Section 13: Disposal Considerations

Disposal Methods: Dispose in accordance with all applicable federal, state/regional and local laws and regulations.

Disposal of Contaminated Packaging: Dispose of unused product properly. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Component Waste Numbers: The U.S. EPA has not published waste numbers for this product's components.

### Section 14: Transport Information

#### International Regulation

IATA: Not regulated as a dangerous good.

# SAFETY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

IMDG: Not regulated as a dangerous good.  
 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: This product is not intended to be transported in bulk.

**Domestic Regulation**

DOT: Not regulated as a dangerous good.

**Section 15: Regulatory Information**

**US Federal Regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed

SARA 302 Extremely Hazardous Substances: None contained in product.  
 SARA 304: Not applicable.  
 SARA 311/312: None known.  
 SARA 313: TRI reporting

TSCA: All components of this product are listed on TSCA Inventory.

**US State Regulations**

Massachusetts Right-to-Know - Substance List: Not regulated  
 New Jersey Worker and Community Right-to-Know Act: Not listed  
 Pennsylvania Worker and Community Right-to-Know Law: Not listed  
 Rhode Island Right-to-Know: Not regulated

California Proposition 65: This product does not contain any chemicals known by the State of California to cause cancer or reproductive harm.

**Component Analysis – International Inventories**

Component	CAS	US	CA	EU	AU	PH	JP	KR	CN	NZ
Octamethylcyclotetrasiloxane (Impurity)	556-67-2	Yes	DSL	EINECS	Yes	Yes	Yes	Yes	Yes	Yes

**Section 16: Other Information**

Issue Date: 3/13/15  
 Revision: 1  
 NFPA Ratings:

Health: 1  
 Fire: 1  
 Reactivity: 0



Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe



# SAFTEY DATA SHEET

Product Identifier: ASI Aquarium Aluminum

Document #: SDS 08817-1

Revision: 1

HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = Not Significant, 1 = Slight, 2 = Moderate, 3 = High, 4 = Extreme, \* = Chronic

Key/Legend:

AICS (Australia); DSL (Canada); IECSC (China); REACH (European Union); ENCS (Japan); ISHL (Japan); KECI (Korea); NZIoC (New Zealand); PICCS (Philippines); TCSI (Taiwan); TSCA (USA); ACGIH – USA. ACGIH Threshold Limit Values (TLV); NIOSH REL – USA. NIOSH Recommended Exposure Limits; OSHA P0 – USA. OSHA – TABLE Z-1 Limits for Air Contaminants – 1910.1000; OSHA Z-1 – USA. Occupational Exposure Limits (OSHA) – Table Z-1 Limits for Air Contaminates; OSHA Z-3 – USA. Occupational Exposure Limits (OSHA) – Table Z-3 Mineral Dusts; ACGIH / TWA – 8-hour, time-weighted average; NIOSH REL / TWA – Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek; NIOSH REL / ST – STEL – 15-minute TWA exposure that should not be exceeded at any time during a workday; OSHA P0 / TWA - 8-hour, time-weighted average; OSHA Z-1 / TWA - 8-hour, time-weighted average; OSHA Z-3 / TWA - 8-hour, time-weighted average

Disclaimer:

The information contained herein is based on data considered accurate which has been obtained from other companies and organizations.

**End of Document**